



Features

Relay interface modules for use with I-7000 remote I/O modules

- **RM-38.61**


6.2 mm wide, 1 pole and 35 mm rail (EN 50022) mounting

Supplied with integral coil indication and protection circuit

Instant removal of relay using plastic retaining clip



Specifications

Model	RM-38.61
Description	Relay Interface Modules 6 A For PLC systems. LED and coil protection modules. Instant removal of relay using plastic retaining clip.
Contact Specification	
Contact configuration	1CO (SPDT)
Rated current (A)	6
Nominal voltage/Max voltage(V)	250 / 400
Rated load in AC1 (VA)	1500
Standard contact material	AgSnO2
Coil Specification	
Nominal voltage (V DC)	24
Rated DC power (mW)	0.17
Technical Data	
Insulation according to EN 61810-5	3.6 kV/3
Surge test (1.2/50µs) between coil and contacts (kV)	6 (8 mm)
Dielectric strength: open contacts (V AC)	1000
Mechanical life AC/DC (cycles):	-/10 · 10 ⁴
Electrical life at rated load in AC1 (cycles)	60 · 10 ³
Ambient temperature range (°C)	-40...+70
Approvals: (according to type)	
Unit weight (g)	31
Boxed quantity (units)	5
Sockets	-
Accessories	-
Dimensions (mm)	76.5 x 6.5 x 89

info@logicbus.com.mx

www.logicbus.com.mx

Alcalde #1822 Col. Miraflores C.P. 44270 Guadalajara, Jal. Mexico
 MX 01 (33) 3854-5975 y 3823-4349 USA 001 (858)-869-5401 (Chula Vista, CA. Office)