



¡ Tu Sitio de Automatización !



RM-48 series

Relay Interface Modules

Features

Relay interface modules for use with I-7000 remote I/O modules

- **RM-48.61**

15.5 mm wide, 1 pole (48.61), and 35 mm rail (EN 50022) mounting

- **RM-48.62**

15.5 mm wide, 2 pole (48.62) and 35 mm rail (EN 50022) mounting

Supplied with integral coil indication and protection circuit

Instant removal of relay using plastic retaining clip





info@logicbus.com.mx

www.logicbus.com.mx

Alcalde #1822 Col. Miraflores C.P. 44270 Guadalajara, Jal. Mexico
MX 01 (33) 3854-5975 y 3823-4349 USA 001 (858)-869-5401 (Chula Vista, CA. Office)

Specifications

Model	RM-48.61	RM-48.62
Description	Relay Interface Modules 10 - 16 A For PLC systems. LED and coil protection modules. Instant removal of relay using plastic retaining clip.	
Contact Specification		
Contact configuration	1CO (SPDT)	2CO (DPDT)
Rated current (A)	16	10
Nominal voltage/Max voltage(V)	250 / 400	
Rated load in AC1 (VA)	4000	2500
Standard contact material	AgNi/AgCdO	AgNi
Coil Specification		
Nominal voltage (V DC)	24	
Rated DC power (mW)	0.65	
Technical Data		
Insulation according to EN 61810-5	3.6 kV/3	
Surge test (1.2/50µs) between coil and contacts (kV)	6 (8 mm)	
Dielectric strength: open contacts (V AC)	1000	1000
Mechanical life AC/DC (cycles)	10 · 10 ⁶ /20 · 10 ⁶	
Electrical life at rated load in AC1 (cycles)	200/100 · 10 ³	150/100 · 10 ³
Ambient temperature range (°C)	-40...+70	
Approvals: (according to type)	GOST  	
Unit weight (g)	65	
Boxed quantity (units)	10	
Sockets	-	
Accessories	-	
Dimensions (mm)	75 x 15.5 x 78.5	

info@logicbus.com.mx

www.logicbus.com.mx

Alcalde #1822 Col. Miraflores C.P. 44270 Guadalajara, Jal. Mexico
 MX 01 (33) 3854-5975 y 3823-4349 USA 001 (858)-869-5401 (Chula Vista, CA. Office)