

Features:

1. Fast response and high accuracy, ideal for field or lab application.
2. Completes with 1 m cable with BNC, Spade Lug or DIN 7 pin connector and wetting bottle to extend electrode life.

Specifications:

	Model	Range	Temp.	Type Ref.	Junction	Refillable	Body	Connector	Size(m m)	Cable
pH	LBPW 2540	0-14	0-80°C	Ag/AgCl	Ceramic	No	PC	BNC	165x12	1 m
	LBPY 2541	0-14	0-80°C	Ag/AgCl	Ceramic	No	PC	BNC	160x12	1 m
	LBGL 2542	0-14	0-90°C	Ag/AgCl	Ceramic	Yes	Glass	BNC	155x12	1 m
	LBGL 2543	0-14	0-90°C	Ag/AgCl	Ceramic	Yes	Glass	BNC	155x12	1 m
	LBTP 2546P (w/Pt100)	0-14	0-80°C	Ag/AgCl	Ceramic	No	PC	BNC+3.5φPlug	160x12	1 m
	LBTP 2546T (w/Thermistor)	0-14	0-80°C	Ag/AgCl	Ceramic	No	PC	BNC+3.5φPlug	160x12	1 m
	LBPF 2547	0-14	5-80°C	Ag/AgCl	Cricoid Teflon	No	PVC	BNC	106x15	1 m
	LBID 254410	0-14	5-90°C	Ag/AgCl	Ground glass sleeve	No	Glass	Spade Lug	160x12	1.2 m
	LBID 254420R	0-14	5-90°C	Ag/AgCl	Ground glass sleeve	Yes	Glass	Spade Lug	160x12	5.0 m
	LBID 254510	0-14	5-90°C	Ag/AgCl	Ground glass sleeve	No	Glass	Spade Lug	155x12	1 m
	LBID 254520	0-14	0-80°C	Ag/AgCl	Cricoid Teflon	No	PPS	Spade Lug	176x16	3 m
	LBID 254520F	0-14	0-80°C	Ag/AgCl	Cricoid Teflon	No	PPS	Spade Lug	176x16	3 m
	Holder Material: PVC Size: 230 x 38 mm(for LB254510 & LB254511)									

	Model	Range	Temp.	Type Ref.	Junction	Refillable	Body	Connector	Size(mm)	Cable
ORP	LBPO25 50	±1500mV	0-80°C	Ag/AgCl	Ceramic	No	PC	BNC	160x12	1 m
	LBGO 2551	±1500mV	0-80°C	Ag/AgCl	Ceramic	Yes	Glass	BNC	160x12	1 m
	LBID 254511	±1500mV	5-90°C	Ag/AgCl	Ground glass sleeve	No	Glass	Spade Lug	155x12	1 m
	LBID 254521	±1500mV	0-80°C	Ag/AgCl	Cricoid Teflon	No	PPS	Spade Lug	176x16	3 m

	Model	Range	Temp.	Type Ref.	Junction	Refillable	Body	Connector	Size(mm)	Cable
Cell	LBCD 2560	K=1.0	0-90°C	N/A	Pt plate	N/A	Glass	BNC	155x12	1 m
	LBCD 2560 P(w/Pt100)	K=1.0	0-90°C	N/A	Pt plate	N/A	Glass	DIN 7 pin	155x12	1 m
	LBCD 2560T (w/Thermistor)	K=1.0	0-90°C	N/A	Pt plate	N/A	Glass	DIN 7 pin	155x12	1 m



LBPW2540 LBPY2541 LBGL2542 LBGL2543 LBID254420R



LBTP2546 LBPF2547 LBPO2550 LBGO2551 LBID2560



HOLDER LBID254510 LBID254511 LBID254520 LBID254521

info@logicbus.com.mx

www.logicbus.com.mx

Alcalde #1822 Col. Miraflores C.P. 44270 Guadalajara, Jal. Mexico
MX 01 (33) 3854-5975 y 3823-4349 USA 001 (619)-884-94-93 (San Diego, CA. Office)