



Pantalla HMI touchscreen TFT de 10.4"

Specifications

Model	LBMT504500T
Performance specification	
Display	10.4" TFT(211.2×158.4mm)
Resolution	640*480 pixels
Color	65536 colors
Backlight	2 CCFL
Brightness	400cd/m ²
Backlight life	50000 hr.
Touch Panel	4-wire precision resistance network
Processor	32-bit RISC CPU 400MHz
Memory	8M FLASH, 16M SDRAM
Recipe memory & RTC	256KB & RTC
Printer port	1 DB25, Support SPRT SP-DN16PH, HP LaserJet P2014, EPSON LQ 305KT
Ethernet	No
Program download	1 USB SLAVE port
COM port	COM0:RS232/RS485-2/RS485-4, COM1:RS232/RS485-2/RS485-4, COM2:RS232
Electrical specification	
Rated power	10.8W

Rated voltage	DC24V
Input range	DC21~DC28V
Power down allowed	<5ms
Insulation resistance	Greater than 50MΩ@ 500V DC
Dielectric strength test	500 VAC 1 minute
Structure specification	
Shell color	Deep gray
Shell material	ABS
Dimensions(mm)	310× 230 × 54
Cutout size(mm)	298 × 218
Weight	1.67kg
Environment specification	
Operating temperature	-0~45°C
Operating humidity	10~90% non-condensing
Storage temperature	-10~60°C
Storage humidity	10~90% non-condensing
Shockproof test	10~25Hz (X, Y, Z direction, 2G, 30 minutes)
Cooling method	Natural air cooling
Certification	
Degree of protection	IP65 (front panel)
CE certification	EN61000-6-2:2005 and EN61000-6-4:2007
FCC compatibility	Complies with FCC Class A

Dimensions in [mm]

