

LBPCH8424051-WH25L0-CB0J08

Panel-PC Chassis 24" 1920x1080, 300nits, Intel® Core™ i7/i5/i3/ Celeron Processor



Your Automation Site!



Features

- 24" LCD panel, 1920 x 1080, 250 nits
- Intel® Core™ i7/i5/i3/ Celeron Processor
- Intel® H61
- 2 x DDR3 1333/1600MHz SO-DIMM Slot (up to 16GB)
- 1 x VGA, 1 x HDMI, 2 x COM, 6 x USB2.0
- 2 x LAN, 1 x PS2, Mic-in, Line-Out



Panel	Cell Type / Glass Surface	TFT LCD / Black Anti-Glare, low reflection coating
	Aspec Ratio / Size	wide / 24" viewable diagonal area
	Active Area / Pixel Pitch	531.36(H) x 298.89(V) mm / 0.2768(H) x 0.2768(V) mm
	Native Resolution / Color	1920(H) x 1080(V) / 16.7 Million
	Brighntess / Contrast	250 cd/m ² (typ) / 1000:1
	Response Time	≤ 5 ms
	Viewing Angle (Typical)	H. 170° (- 85° ~ + 85°) , V. 160°(- 80° ~ + 80°)
	Light Source	LED, Long life, 35,000 hrs (typ)
System	CPU	Intel® Core™ i7/i5/i3/ Celeron Processor
	BIOS	UEFI
	System / Graphic Chipset	Intel® HD Graphics (By CPU); Shared Memory
	System Memory	2 x DDR3 1333/1600MHz SO-DIMM Slot (up to 16GB)
	HDD	4 x SATA2
	I/O Ports	1 x VGA
		2 x COM
		1 x HDMI
6 x USB(2.0)		
2 x LAN		
Expansion	1 x Mini PCI-E (Half Size)	
Power	Power Input	ATX PWR (24+4 pin)
	Power Consumption	90 Watt, <1 Watt
Environmental	Operating Temperature	- 5°C~60°C (23°F~140°F)
	Operating Humidity	0%~95% (non-condensing)

Options	Touch	Enhanced Pane	Other	
	Resistive(With Glass)	High Brightness Panel	WiFi	Networking Digital Signage
	Capactive	Panel-LED Backlight	3G	Web Cam
	SAW	Wide Temperature	Bluetooth	Motion Sensor
		Wide Viewing Angle	RFID	Auto LightSensor
		Sunlight Readable		Auto-Dimming



PLCs Acquisition Instruments Data logger Power HMIs Switches Motion Sensors Converters Keyboards SCADA Telemetry

support@logicbus.com

Your automation site!

www.logicbus.com