

**LB-SP-AS/AL** Being mini-sized, light weight, high efficiency, good reliability and so on. In special, it has the remote control and UPS function



### Features

- Compact design, small size and light weight
- Internal EMI filter
- Remote Control Function
- Short-circuit protection and over-load protection
- Certificate : CE Certificate
- High efficiency and good reliability
- Power Output LED Indicator
- Over-heat Protection
- UPS Function

### Property Parameters

Type	LB- SP -05AS	LB-SP -12AS	LB-SP-24AS	LB-SP-05AL	LB-SP-12AL	LB-SP-24AL
Output Voltage	5 V	12 V	24 V	5 V	12 V	24 V
Output Current	5 A	3 A	1.5 A	10 A	6 A	3 A
Dimensions(LxWxH)	71mm×106mm×65mm			126mm×106mm×65mm		
Installation	Standard 35 mm DIN (EN50022-35)					
Full-range Voltage Input	100-240VAC/140-340VDC					
Waving Voltaje Allowance Range	85-264VAC/120-370VDC					
Input Frequency	47-63Hz					
Output Voltaje Stability	≤±0.5%					
Ripple	≤150mVp-p					
Temperatura	-25°C ~ +70°C					
Insulation and Breakdown	>1.5KV					
Efficiency	>75%					